

REQUEST FOR QUOTATION # 2017 - 02
 BACKHOE LOADER WITH EXTENDABLE DIPPERSTICK ATTACHMENT AND FOUR WHEEL DRIVE SPECIFICATION
 FOR PRICING



ADDENDUM 1 (March 27, 2017)
 To Whom it May Concern

Re: RFQ- 2017-02
 - Backhoe Loader with Extendable Dipperstick attachment and four wheel drive

In connection with the above noted project, the following changes have been made (in red):

2.0 BID DEPOSIT

20. Backhoe Equipment		
Automatic hydraulic swing brakes or cushioning shall be supplied		
The backhoe shall be entirely hydraulically controlled with separate cylinders to control the bucket, boom and dipperstick		Specify:
AMI part # LBQT1214PG mechanical pin grab coupler AMI power tilt hydraulic pin grab or equivalent. Quick coupler feature to pick up buckets and attachments shall be supplied.		Specify Make:
Options (Bidders are requested to bid, but not required to bid on any of these options)		Specifications
AMI Power tilt HYD pin grab		\$ _____
Quiktach Front Clam Bucket (1.5 Cubic Yards)		\$ _____
Quiktach Rear Wrist Bucket		
Extended Fender Kit		
5 year/4000 hr. extended power train warranty		\$ _____
5 year/4000 hr. full machine warranty		\$ _____

REQUEST FOR QUOTATION # 2017 - 02
BACKHOE LOADER WITH EXTENDABLE DIPPERSTICK ATTACHMENT AND FOUR WHEEL DRIVE SPECIFICATION
FOR PRICING

Please replace your page 8 and page 11 with the attached amended pages.

If you have any further questions, please contact the undersigned:

Yours Truly

Mike McIsaac
Road Foreman Town of Minto
519-338-2511 ext 234
mike@town.minto.on.ca

1. Backhoe Equipment			
Automatic hydraulic swing brakes or cushioning shall be supplied			
The backhoe shall be entirely hydraulically controlled with separate cylinders to control the bucket, boom and dipperstick			Specify:
AMI power tilt hydraulic pin grab or equivalent. Quick coupler feature to pick up buckets and attachments shall be supplied.			Specify Make:
Backhoe boom lock shall be controlled from the cab			
Auto Idle feature shall be included			Specify:
2. Backhoe Buckets			Specify Make:
AMI part # LBD1214E36 36" ditch cleaning bucket with reversible cutting edge (13.00 cu. ft. capacity), or equivalent shall be supplied			
3. Hydraulic System			Specify:
Open center hydraulic system for efficient operation of the loader and backhoe			
Gear type pumps shall be heavy duty continuous operating type, with 36 U.S. G.P.M. (136 L/min) capacity minimum with hydraulic cooler to facilitate operation of backhoe, loader and any attachments			
All hoses and fittings shall be Oring-flat face seal type located so that they are protected			
Loader auxiliary hydraulics with detent and quick coupler hydraulic fittings shall be included			
Single and dual flow backhoe auxiliary hydraulics with quick coupler hydraulic fittings shall be included to operate single and dual flow attachments			Specify:
4. Counter Weights			
The counterweights recommended by the manufacturer for efficient operation of the extendable dipperstick and coupler shall be supplied			
5. Paint			
Manufacturer's standard colours			

Options (Bidders are requested to bid, but not required to bid on any of these options)		Specifications
Quiktach Front Clam Bucket (1.5 Cubic Yards)		\$ _____
Extended Fender Kit		
5 year/4000 hr. extended power train warranty		\$ _____
5 year/4000 hr. full machine warranty		\$ _____

HLA SNOW

With front loader attachment

Specifications

Part #	Clearing Width Closed (In.)	Clearing Width Open (In.)	Overall Road Width (Angled) (In.)	Snow Clearing Width (Angled) (In.)	Mouldboard Height (In.)	Weight (lbs.)	Max Operating Weight (lbs.)
SB4200W814	93.5	165.5	91	135	34	2,705	25,000
SB4200W915	108	180	102	146	34	2,865	25,000
SB4200W1016	120	192	112	156	34	2,975	25,000
SB4200W1218	144	216	132	176	34	3,175	25,000
SB4200W1420	168	240	152	196	34	3,425	25,000

SB4200W915		\$ _____
Spill Guard		\$ _____
High Tensile Long Wear Skid Shoes		\$ _____
Rubber Cutting Edge		\$ _____
Extra set of blades and hardware		\$ _____